PROMOTECH





PRO-2 PB | COMPACT PIPE BEVELLER

PRO-2 PB is a compact, handy pipe beveller that mills pipes made of carbon and stainless steel, aluminum alloys, and copper-nickels. The machine can face off and bevel pipes from inner diameters (ID) of 19.5 mm (0.77") to outer diameters (OD) of 48 mm (1.89").

Small pipes from ID 15.5 mm (0.61") up to OD 29 mm (1.14") can be beveled with optional small mandrel set.

PRO-2 PB is able to mill also larger pipes from ID 38 mm (1.50") up to OD 60.3 mm (2.37") by means of an optional extension set.

Its exceptionally narrow housing (only 48 mm wide) makes it perfectly suited to space restricted areas such as boiler water walls.

PRO-2 PB incorporates overload systems incl. wet multi-disk friction clutch to prevent gear damage if the tool gets stuck.



3 different sources of power to choose from:









Max wall thickness up to 8 mm (0.32")



ID 19.5 - 38 mm (0.77 - 1.50")
ID 15.5 - 22 mm (0.61 - 0.87") /option/
ID 38 - 58 mm (1.50 - 2.28") /option/



Facing off



Pipe OD beveling up to 48 mm (1.89") up to 60.3 mm (2.37") /option/


TECHNICAL SPECIFICATION	PRO 2 PB with air motor	PRO 2 PB with electric motor	PRO 2 PB with battery motor
Air requirement	0.6 MPa (87 psi)	-	-
Air consumption	1600 l/min (56.5 CFM)	-	-
Voltage	-	1 ~ 220-240 V, 50-60 Hz	18 V DC
Power	800 W	1100 W	-
Connection	CEJN 410 DN 10.4 R 1/2" BSPT fitting for quick-coupling	Electrical plug	Battery connection
Nominal rotational speed	105 rpm	10-134 rpm (gear 1) 30-377 rpm (gear 2)	10-60 rpm (gear 1) 30-205 rpm (gear 2)
Pipe diameter	19.5 mm ID-48 mm OD 15.5 mm ID-29 mm OD* 38 mm ID-60.3 mm OD**	19.5 mm ID-48 mm OD 15.5 mm ID-29 mm OD* 38 mm ID-60.3 mm OD**	19.5 mm ID-48 mm OD 15.5 mm ID-29 mm OD* 38 mm ID-60.3 mm OD**
Maximum pipe wall thickness	8 mm 3.5 mm*	8 mm 3.5 mm*	8 mm 3.5 mm*
Weight with motor	7.6 kg (17 lbs)	7.4 kg (16.5 lbs)	6.5 kg (14.5 lbs), includes battery

- * With an optional small mandrel set (ZST-0731-03-00-00-0).
- ** With an optional extension set (ZST-0731-02-00-00-0).


Standard shipping set:


- Beveling machine (without motor, tool bits)
- Plastic box
- Standard self-centering expandable mandrel for pipe ID \emptyset 19.5 38 mm (0.77-1.50")
- 4 sets of spreaders and 4 expansion sleeves for standard mandrel
- Tool bit holder
- Handle
- Set of tools
- Tool box
- Coolant container with nozzle
- Operator's manual


Dimensions



PRO 2 PB with pneumatic motor







PRO 2 PB with electric motor

Optional accessories:





Adapter and driver ZST-0567-24-00-00-0






Driver ZBI-0567-25-00-00-0

Electric motor SLN-000238 (230 V)













Battery brushless drive WRT-000024





Battery 10.0 Ah AKM-0738-10-00-02-0



Battery charger with built-in Air-Cooled system LDW-0738-10-00-30-0 (EU) LDW-0738-04-00-30-0 (UK)

Charging time: ~ 30 min (4.0 Ah)

~ 41 min (5.5 Ah)

~ 74 min (10.0 Ah)





Air preparation set ZST-000021



HD-CUT OIL 1 - tapping, drilling and machining fluid OLJ-0505-09-00-00-0 (0.5 kg) OLJ-0505-10-00-00-0 (1.0 kg) OLJ-0505-11-00-00-0 (5.0 kg)

Tool bits:

NOZ-000071 for steel	0° facing tool bit short		
NOZ-000078 for stainless steel	0° facing tool bit short*	25	
NOZ-000072 for steel	0° facing tool bit long	707	
NOZ-000079 for stainless steel	0° facing tool bit long*	9 9	
NOZ-000073 for steel	30° beveling tool bit	30°	
NOZ-000080 for stainless steel	30° beveling tool bit*	9	
NOZ-000074 for steel	37.5° beveling tool bit	37.5°	
NOZ-000081 for stainless steel	37.5° bevelling tool bit*	9	
NOZ-000075 for steel	45° beveling tool bit	45°	
NOZ-000082 for stainless steel	45° beveling tool bit*	9	

Small mandrel set for pipes from ID 15.5 mm (0.61") up to OD 29 mm (1.14") ZST-0731-03-00-00-0





Extension set for pipes from ID 38 mm (1.50") up to OD 60.3 mm (2.37") ZST-0731-02-00-00-0



