R PROMOTEC

PRO-36 COMPACT DRILLING MACHINE



The PRO-36 makes holes up to 36 mm in diameter by using annular cutters. The machine can also drill holes up to 12 mm in diameter by means of twist drill bits with Weldon shank 19mm(3/4").

Compact design and excellent ratio weight/power make this mag drill a very popular choice for customers.



- Maintenance-friendly design makes it easy to use
- Magnetic Field Shape Control (MFSC) provides maximum holding power on thin materials
- Magnetic Power Adhesion Control (MPAC) detects adhesive force of electromagnetic base and protects both the machine and the operator from work on too thin work piece



Core drill

max 36 mm





Twist drill: max 12 mm (1/2") with Weldon Shank 19mm (3/4")







Power

1020 W



Weight 10 kg

Depth of cut 51 mm

Stroke 70 mm 350 rpm



PRO-36 TECHNICAL SPECIFICATION	
Motor Speed (under load)	350 rpm
Power	1020 W
Weight	10 kg
Max milling capacity	36 mm (1 7/16")
Max drilling capacity	12 mm (1/2")
Max countersinking	40 mm (1 9/16")
Stroke	70 mm (2 3/4")
Max depth of cut	51 mm (2")
Voltage	1~ 220-240 V, 50-60 Hz 1~ 110-120 V, 50-60 Hz
MPAC (Magnetic Power Adhesion Control)	yes
MFSC (Magnetic Field Shape Control)	yes
Magnetic clamping force (surface with the thickness of 25 mm and roughness Ra = 1.25)	917 kgf (9000 N)
Magnet Base Dimensions	80 x 161 x 36,5 [mm] 3-1/8 x 6-5/16 x 1-7/16 ["]
Min. Workpiece Thickness	6 mm (1/4")
Tool holder	19 mm (3/4") Weldon
Product Code 230V/50Hz	WRT-0440-10-20-00-4
Product Code 115V/60Hz	WRT-0440-10-10-00-4

Standard shipping set:

- Magnetic Base Drilling Machine
- Plastic Box
- Swarf Shield/Cutter Guard
- Coolant Bottle Assembly
- Safety Chain with Snap Hook
- Allen wrench hex s=4
- Operator's Manual
- Standard shipping weight 16,7 kg (36 lbs)

Selected additional accessories:

- UKL-0440-16-00-00-0 Coolant System 2l
- PDS-0587-10-00-00-0 Vacuum pad


You

Þ

- ZSP-0587-11-00-00-0 Compressed air ejector
- PDS-0110-10-00-01-0 Pipe attachment DMP 250 for pipes with diameters of 80-250 mm (3-10")









Pipe attachment DMP 250



Vacuum pad

Coolant System 2l



Compressed air ejector



PROMOTECH Sp. z o.o. ul. Elewatorska 23/1, 15-620 BIAŁYSTOK, POLAND tel. (+48 85) 678 34 05, fax (+48 85) 662 78 77 marketing@promotech.eu www.promotech.eu Your local dealer: